



SF Subfreezing Dryers 360-420 m³/h, 212-247 cfm

Ranging from 212 to 247 cfm, SF-Series subfreezing dryers are designed specifically for Class-3 quality air. This unique dryer combines the cost-effective operation of refrigerated technology with the performance of desiccant dryers for a very low total cost of ownership.

Features

- **Affordable High Quality Air:** ISO Class-3 air quality with a -20°C (-4°F) PDP delivered without interruption over the full range of compressor utilization
- **Lower Cost of Ownership:** Patented heat exchanger design provides a subfreezing PDP without the need of purge air for regeneration, lowering energy and operating costs
- **Low Temperature Operation:** Ideal for systems that have piping or pneumatic equipment exposed to subfreezing temperatures
- **Smart Control:** Advanced controller ensures high air quality through an intuitive high-resolution display and remote connectivity to onboard web pages
- **Reduced Maintenance:** No costly consumables such as drum wheels or desiccant wheels that require replacement, lowering maintenance costs



Model Specifications

Model	Capacity m ³ /hr (scfm)	Operating Power kW	Length x Width x Height mm (in)	Weight kg (lb)	Connection Air In/Out
D360SF-A	360 (212)	1.46	1063 (41.8) x 899 (35.4) x 1767 (69.6)	352 (776)	1 1/2" BSP
D420SF-A	420 (247)	1.78	1063 (41.8) x 899 (35.4) x 1670 (65.7)	352 (776)	1 1/2" BSP



About Ingersoll Rand Inc. Ingersoll Rand Inc. (NYSE:IR), driven by an entrepreneurial spirit and ownership mindset, is dedicated to helping make life better for our employees, customers and communities. Customers lean on us for our technology-driven excellence in mission-critical flow creation and industrial solutions across 40+ respected brands where our products and services excel in the most complex and harsh conditions. Our employees develop customers for life through their daily commitment to expertise, productivity and efficiency. For more information, visit www.IRCO.com.